

TS2000 Activity Analysis Quick Start Installation Guide

Introduction

This document outlines the installation process for TS2000 Activity Analysis. It should be used by a system administrator already familiar with the concepts described in the TS2000 Activity Analysis Installation Guide. Default file locations are shown. These should be adjusted to take account of your own environment.

Uninstalling Previous Versions

Use the Internet Services Manager to select the TS2000 Web Site or Virtual Directory. From the Properties tab click on the Remove button.

Use Component Services to navigate to and right-click on IIS-{Default Web Site//Root/ts2000} and select Shut down.

From Control Panel Add/Remove Programs scroll to CHL TS2000 Activity Analysis and click the Remove button.

Installing the software

Insert the TS2000 Activity Analysis CD into the CD drive. If autorun does not start automatically, use Windows Explorer to navigate to the CD ROM and double-click on the Setup icon.

Respond to the Installer prompts: License, Install location and Install.

Database Installation Scripts

Run the Database Install Scripts from a Command Prompt, default C:\Program Files\TS2000\Scripts, by typing:

```
CREATE_TS2000_LSC_DATABASE <SQL Server login> <password>
```

The script pauses after displaying a dialog, press any key to run it, or Ctrl-C to abort

Alternatively, load and run each script individually from within SQL Server Enterprise Manager. The scripts are:

```
99_TS2000_DELETE_DATABASE.sql – only use to drop old copy
01_TS2000_CREATE_DATABASE.sql
02_TS2000_CREATE_TS2000_USER.sql
10_TS2000_CREATE_TABLES_AND_INDICES.sql
30_TS2000_INSERT_BASE_DATA.sql
39_LSC_INSERT_SAMPLE_DATA.sql
```

Create the TS2000 Web Site or Virtual Directory

Configure the Web Server from a Command Prompt, default C:\Program Files\TS2000\Scripts, by typing:

```
MAKE_TS2000_IIS "TS2000 Activity Analysis" "C:\InetPub\wwwroot"  
<host_name>
```

The script pauses after displaying a dialog, press any key to run it, or Ctrl-C to abort

Click OK when the Windows Script Host prompts appear (twice)

Alternatively, configure the web site or a virtual directory manually, and assign the TS2000 Installer folder location to it. The default location for TS2000 is C:\InetPub\wwwroot.

IIS Setting for TS2000

The following Administrative Settings should be set for the TS2000 Activity Analysis web site or virtual directory from the Internet Services Manager

Dialog	Setting
Properties dialog	TCP Port value, default 80
Home directory tab	Read enabled, disable logging and indexing Execute permissions set to scripts only Inheritance overrides, define child nodes for TS2000
Configuration button	From App Options tab disable session state

Configuring Microsoft Data Link

1. Configure the Web Server from Windows Explorer, default C:\InetPub\wwwroot\db, by double clicking on the ts2000dlk icon and setting:

1. Server name
2. Specific user name and password – user name: TS2000, password, leave blank, set 'leave blank' checkbox
3. Select the database on the server – TS2000

Click the test connection button

Test the TS2000 Activity Analysis Login

Test the login with:

```
http://<host_name>/TS2000/systemCheck.asp
```